

BONDTECH

Rubber & Composites

The Rubber Industry



Features

Heating Systems

- **Indirect Heat** : Electric or Indirect Steam
- **Direct Heat** : Direct Steam

Quick Opening Door

- Hydraulic powered door for quick and save open/lock
- Locking ring rotation only – Extends gasket life
- O-ring gasket – Long lasting
- No air system required for gasket seal

Controls

Basic Temperature/Pressure Controls

- Prepackaged in C/S Nema 12 Enclosure
- 24 hour circular chart recorder

Programmable Logic Controller (PLC)

- Maximum flexibility to program autoclave process cycle
- Optimization of autoclave cycle for desired results
- Effective tool for achieving high quality products
- Modem hookup capabilities

Custom Engineering

- In-house Engineering
- Customize Engineering Capabilities
- Manufactured to your special capabilities

Vessel Specifications:

Pressure	90-150 PSIG +1/16 corrosion allowance
Size	Per customer specifications
Door	Hydraulic quick opening, manual swing
Loading	Horizontal loading arrangement

Quality Control and Safety

- ASME & National Board Certified
- Safety interlocks
- Safety relief valve
- Complete acceptance testing prior to shipment
- Engineers available for on-line technical support



Contact Us:

1278 Hwy 461
Somerset, KY 42503
Toll Free: 800-414-4231
Direct: 606-677-2616
Fax: 606-676-9157

Web: <http://www.bondtech.net>
Email: elsabrown@earthlink.net